

## 1.3MP IP Dome - HW-IP1.3MPD-P



### Description:

- \* Day/night functionality
- \* Optical glass window with higher light transmittance
- \* IR anti-reflection window to increase the infrared transmittance
- \* Up to 30 m (98 ft) IR distance
- \* 3D noise reduction

### Features:

- 1/3" progressive scan CMOS
- Up to 1280×960 resolution, 30fps
- 2.8mm/3.6mm/6mm optional
- Smart IR, up to 30m IR distance
- 3D DNR, ONVIF
- DC12V, PoE. Wide voltage range of  $\pm 25\%$
- IP66

## 1.3MP IP Dome With POE - HW-IP1.3MPD-P

### Specifications :

Sensor	1/3", 1.3 megapixel, progressive scan, CMOS
Lens	2.8mm@F1.8 Angle of view(H): 99.1°
Shutter	Auto/Manual, 1/6~1/8000 s
Day/Night	IR-cut filter with auto switch (ICR)
IR	30m (98 ft) IR range
AWB(Auto white balance)	Auto/manual
Gain Control	Auto/manual
WDR	Digital
Noise Reduction	2D/3D
<b>Video</b>	
Max. Resolution	1280×960
Video Compression	H.264/MJPEG
Frame Rate	960P (1280×960): Max. 30 fps; 720P (1280×720): Max. 30 fps; D1 (720×576): Max. 25 fps
Video Streaming	Triple
OSD	Up to 8 OSDs
Motion Detection	Up to 2 areas
Privacy Mask	Up to 4 areas
<b>Network</b>	
Protocols	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,Qos,DNS,DDNS,NTP,FTP,UPnP,HTTP
Compatible Integration	ONVIF
<b>Interface</b>	
Network	10M/100M Base-TX Ethernet
<b>General</b>	
Power	12 V DC, or PoE (IEEE802.3 af)
	Power consumption: 3.5 W (5.5W with IR on)
Dimensions (∅ x H)	∅126 x 94 mm (∅5.0" x 3.7")
Weight	0.33 kg (0.73 lb)
Working Environment	-35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 90% RH(non-condensing)
Ingress Protection	IP66