

4MP IP Dome - HW-IP4MPD-P



Description:

- * Day/night functionality
- * Up to 120 dB WDR (Wide Dynamic Range)
- * Smart IR, up to 30 m (98 ft) IR distance
- * Wide temperature range: -35°C to 60°C (-31°F to 140°F)
- * Wide voltage range of $\pm 25\%$

Features:

- 1/3" progressive scan CMOS
- 2560 x 1440 resolution, 25fps
- 2.8mm/3.6mm/6.0mm optional
- Smart IR, up to 30m IR distance
- H.265, 3D DNR, ROI, 9:16 corridor mode, ONVIF
- DC12V, PoE. Wide voltage range of $\pm 25\%$
- IP66

4MP IP Dome - HW-IP4MPD-P

Specifications :

Sensor	1/3", 4 megapixel, progressive scan, CMOS
Lens	2.8mm@F1.8 Angle of view(H): 112.5°
Min. Illumination	Colour: 0.02 Lux (F1.8, AGC ON) 0 Lux with IR
Shutter	Auto/Manual, 1/6~1/8000 s
Day/Night	IR-cut filter with auto switch (ICR)
IR	30m (98 ft) IR range
AWB(Auto white balance)	Auto/manual
Gain Control	Auto/manual
WDR	120 dB
Noise Reduction	2D/3D
Video	
Max. Resolution	2592×1520
Video Compression	H.265, H.264, MJPEG
Frame Rate	4MP (2592×1520): Max. 20 fps; 4MP (2560×1440): Max. 25 fps 3MP (2048×1520): Max. 30 fps; 1080P (1920×1080): Max. 30 fps
Video Streaming	Triple
OSD	Up to 8 OSDs
9:16 Corridor Mode	Supported
Motion Detection	Up to 2 areas
Privacy Mask	Up to 4 areas
Network	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, SIP, QoS
Compatible Integration	ONVIF, API
Interface	
Network	10M/100M Base-TX Ethernet
General	
Power	12 V DC, or PoE (IEEE802.3 af)
	Power consumption: Max 5.5 W
Dimensions (Ø x H)	Φ126 x 94 mm (Ø5.0" x 3.7")
Weight	0.33 kg (0.73 lb)
Operating Conditions	-35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP66