

1.3MP IP Bullet - HW-IP1.3MPB-P



Description:

- * Day/night functionality
- * Optical glass window with higher light transmittance
- * IR anti-reflection window to increase the infrared transmittance
- * 3D DNR (Digital Noise Reduction)

Features:

- 1/3" progressive scan CMOS
- Up to 1280 x 960 resolution, 30fps
- 3.6mm/6mm optional
- Smart IR, up to 30m IR distance
- 3D DNR, ONVIF
- DC12V, PoE. Wide voltage range of $\pm 25\%$
- IP66

1.3MP IP Bullet - HW-IP1.3MPB-P

Specifications :

Sensor	1/3", 1.3 Megapixel, progressive scan, CMOS	
Lens	3.6mm@F1.8 Angle of view(H): 76.7°	6mm@F1.8 Angle of view(H): 46.9°
Shutter	Auto/Manual, 1/6~1/8000 s	
Day/Night	IR-cut filter with auto switch (ICR)	
IR	Up to 30m (98 ft) IR range	
AWB(Auto white balance)	Auto/manual	
Gain Control	Auto/manual	
WDR	Digital	
Noise Reduction	2D/3D	
Video		
Max. Resolution	1280×960	
Video Compression	H.264/MJPEG	
Frame Rate	960P (1280*960): Max. 30 fps; 720P (1280*720): Max. 30 fps; D1 (720*576): Max. 25 fps	
Video Streaming	Triple	
OSD	Up to 8 OSDs	
Motion Detection	Up to 2 areas	
Privacy Mask	Up to 4 areas	
Network		
Protocols	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,Qos,DNS,DDNS,NTP,FTP,UPnP,HTTP	
Compatible Integration	ONVIF	
Interface		
Network	10M/100M Base-TX Ethernet	
General		
Power	12 V DC, or PoE (IEEE802.3 af)	
	3.5 W (5.5W with IR on)	
Material	Plastics	
Dimensions (L × W × H)	146 × 82.4 × 71.7 mm (5.7" × 3.2" × 2.8")	
Weight	0.26 kg (0.57 lb)	
Working Environment	-35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 90% RH(non-condensing)	
Ingress Protection	IP66	